

REVISED VERSION

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
30 November 2000 (30.11.2000)

PCT

(10) International Publication Number
WO 00/72549 A3

- (51) International Patent Classification⁷: H04L 29/06, 12/56
- (74) Agents: WILLIAMS, David, J. et al.; Lucent Technologies UK Limited, 5 Mornington Road, Woodford Green, Essex IG8 0TU (GB).
- (21) International Application Number: PCT/GB00/01330
- (81) Designated States (*national*): AU, BR, CA, CN, ID, IN, JP, KP, KR, US.
- (22) International Filing Date: 7 April 2000 (07.04.2000)
- (25) Filing Language: English
- Published:
— with international search report
- (26) Publication Language: English
- (88) Date of publication of the international search report:
9 August 2001
- (30) Priority Data:
99304034 25 May 1999 (25.05.1999) EP
- Date of publication of the revised international search report:
8 November 2001
- (71) Applicant (*for all designated States except US*): LUCENT TECHNOLOGIES INC. [US/US]; 600 Mountain Avenue, Murray Hill, NJ 07974-0636 (US).
- (15) Information about Correction:
see PCT Gazette No. 45/2001 of 8 November 2001, Section II
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): YANG, Lin [CN/GB]; 6 Obcron Way, Abbey Meads, Swindon, Wiltshire SN2 3WH (GB).
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: METHOD AND APPARATUS FOR TELECOMMUNICATIONS USING INTERNET PROTOCOL



(57) Abstract: In a wireless packet switching telecommunications network, voice services are provided by having a compressor/decompressor in each mobile station to provide each voice packet with a compressed header. Voice data and signalling data are sent separately and in different data formats to the air interface. The compressed header may be an M bit and a cyclically reset timeclock_number, which is decompressed by use of a wallclock which counts reset cycles to reinstate the voice packet headers. Alternatively, RTP agents are provided at the compression and decompression points, and voice packets are sent without headers over a "high quality" network such as a frame relay or ATM network. Compression state of a voice packet header can be established by sending call set-up information over an out-of-band channel between compression points in a mobile station and in the network.

WO 00/72549 A3

BEST AVAILABLE COPY

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 00/01330

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04L29/06 H04L12/56

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04L H04M H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, PAJ, EP0-Internal, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 820 168 A (TEXAS INSTRUMENTS INC) 21 January 1998 (1998-01-21) page 4, line 40 -page 6, line 20 page 8, line 13 - line 28 page 9, line 22 - line 33 page 11, line 38 - line 48 page 18, line 35 - line 48 page 27, line 5 -page 28, line 53 page 39, line 20 - line 25 page 39, line 20 - line 25; figures 2B-D,3C,7B,7C	22
A	page 39, line 20 - line 25; figures 2B-D,3C,7B,7C --- -/--	1,8

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

2 August 2001

Date of mailing of the international search report

07. 08. 2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3018

Authorized officer

Heinrich, D

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 00/01330

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 841 831 A (AT & T CORP) 13 May 1998 (1998-05-13) column 1, line 5 -column 4, line 30; figures 2B-D,3C,7B,7C column 5, line 50 -column 6, line 17; figures 2B-D,3C,7B,7C column 7, line 15 - line 35; figures 2B-D,3C,7B,7C column 7, line 15 - line 35; figure 1 column 7, line 15 - line 35; figure 1	22
Y		1-4,6,8, 13
A	column 7, line 15 - line 35; figure 1 ---	5,7
Y	WO 98 37665 A (VAZIRI FARAMARZ ;WIMSATT JOHN D (US); FONEFRIEND SYSTEMS INC (US)) 27 August 1998 (1998-08-27) page 1, line 6 -page 3, line 1; figure 1 page 5, line 4 -page 6, line 21; figure 1 page 8, line 4 - line 10; figure 1 page 10, line 22 -page 11, line 1; figure 1 page 17, line 8 - line 10; figure 1 page 18, line 4 -page 19, line 9; figure 1 page 28, line 7 -page 29, line 5; figure 1 page 39, line 12 - line 22; figure 1 page 43, line 19 -page 44, line 12; figure 1 page 43, line 19 -page 44, line 12; figure 2A page 43, line 19 -page 44, line 12; figure 2A ---	1-4,6,8, 13
A		5,7,22
Y	S.CASNER,V.JACOBSON: "Compressing IP/UDP/RTP Headers for Low-Speed Serial Links" NETWORK WORKING GROUP. February 1999 (1999-02), pages 1-22, XP002121319 cited in the application the whole document ---	1,4,6,8, 13
A		2,3,5,7, 17-21
Y	SRIDHAR T PAI: "IP Telephony: Need for Standards" VOICE & DATA, 21 May 1999 (1999-05-21), pages 1-3, XP002121320 the whole document line 12; figure 2A ---	1,4,6,8, 13
A		2,3,5,7
	--- -/--	

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 00/01330

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 5 841 854 A (MELAMPY PATRICK J ET AL) 24 November 1998 (1998-11-24) column 1, line 13 - line 16; figure 2A column 4, line 20 - column 6, line 8; figure 2A column 7, line 36 - line 42; figure 2A column 8, line 25 - line 36; figure 2A column 10, line 47 - column 12, line 34; figure 2A column 13, line 31 - column 14, line 4; figure 2A column 15, line 10 - line 13; figure 2A column 16, line 36 - line 43; figure 2A column 18, line 1 - line 7; figure 2A ---</p>	1,8,22
A	<p>EP 0 917 328 A (LUCENT TECHNOLOGIES INC) 19 May 1999 (1999-05-19) page 1, paragraph 8 - line 7; figure 2A page 6, paragraph 31 - line 7; figure 2A page 7, paragraphs 38,39 - line 7; figure 2A page 11, paragraphs 68,69 - line 7; figure 2A page 15, paragraph 94 - line 7; figure 2A page 17, paragraph 115 - line 7; figure 2A page 18, paragraphs 117,126 - line 7; figure 2A page 22, paragraphs 155,157 - line 7; figure 2A page 24, paragraphs 161,162 - line 7; figure 2A page 26, paragraph 166 - line 7; figure 2A page 30, paragraph 191 - line 7; figure 2A page 35, paragraph 237 - line 7; figure 2A page 35, paragraph 237 - line 7; figure 2A -----</p>	1,8,22

INTERNATIONAL SEARCH REPORT

national application No.
PCT/GB 00/01330

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:

2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:

3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this International application, as follows:

see additional sheet

As a result of the prior review under R. 40.2(e) PCT,
no additional fees are to be refunded.

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.

2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.

3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:

4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; It is covered by claims Nos.:

Remark on Protest

- ☒ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-16,22

A device and a method for a packet switching radio network to provide voice services, where said device and method operate according to RTP/UDP/IP, and where said device and method comprise out-of-band signalling and compression of transmittable material.

2. Claims: 17-21

A method for compressing and decompressing headers, where said method comprises utilizing increasing counts and timestamps for performing said decompression.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 00/01330

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0820168 A	21-01-1998	US 6002722 A JP 10154949 A	14-12-1999 09-06-1998
EP 0841831 A	13-05-1998	CA 2217838 A JP 10173696 A	07-05-1998 26-06-1998
WO 9837665 A	27-08-1998	AU 6666898 A EP 0966815 A	09-09-1998 29-12-1999
US 5841854 A	24-11-1998	US 5862208 A US 5566236 A	19-01-1999 15-10-1996
EP 0917328 A	19-05-1999	CA 2249817 A CA 2249830 A CA 2249831 A CA 2249836 A CA 2249837 A CA 2249838 A CA 2249839 A CA 2249862 A CA 2249863 A EP 0912026 A EP 0910198 A EP 0917320 A EP 0917318 A EP 0912027 A EP 0912012 A EP 0918417 A EP 0912017 A JP 11289353 A JP 11252183 A JP 11275154 A JP 11275155 A JP 2000022758 A JP 11275156 A JP 11275157 A JP 11284666 A JP 11331276 A	14-04-1999 14-04-1999 14-04-1999 14-04-1999 14-04-1999 14-04-1999 14-04-1999 14-04-1999 14-04-1999 28-04-1999 21-04-1999 19-05-1999 19-05-1999 28-04-1999 28-04-1999 26-05-1999 28-04-1999 19-10-1999 17-09-1999 08-10-1999 08-10-1999 21-01-2000 08-10-1999 08-10-1999 15-10-1999 30-11-1999

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
30 November 2000 (30.11.2000)

PCT

(10) International Publication Number
WO 00/72549 A3

(51) International Patent Classification⁷: **H04L 29/06**,
12/56

6 Oberon Way, Abbey Meads, Swindon, Wiltshire SN2
3WH (GB).

(21) International Application Number: PCT/GB00/01330

(74) Agents: WILLIAMS, David, J. et al.; Lucent Technolo-
gies UK Limited, 5 Mornington Road, Woodford Green,
Essex IG8 0TU (GB).

(22) International Filing Date: 7 April 2000 (07.04.2000)

(25) Filing Language: English

(81) Designated States (national): AU, BR, CA, CN, ID, IN,
JP, KP, KR, US.

(26) Publication Language: English

(30) Priority Data:
99304034 25 May 1999 (25.05.1999) EP

Published:
— with international search report

(71) Applicant (for all designated States except US): LU-
CENT TECHNOLOGIES INC. [US/US]; 600 Mountain
Avenue, Murray Hill, NJ 07974-0636 (US).


(88) Date of publication of the international search report:
9 August 2001

(72) Inventor; and

(75) Inventor/Applicant (for US only): YANG, Lin [CN/GB];

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR TELECOMMUNICATIONS USING INTERNET PROTOCOL



(57) Abstract: In a wireless packet switching telecommunications network, voice services are provided by having a compressor/decompressor in each mobile station to provide each voice packet with a compressed header. Voice data and signalling data are sent separately and in different data formats to the air interface. The compressed header may be an M bit and a cyclically reset timeclick_number, which is decompressed by use of a wallclock which counts reset cycles to reinstate the voice packet headers. Alternatively, RTP agents are provided at the compression and decompression points, and voice packets are sent without headers over a "high quality" network such as a frame relay or ATM network. Compression state of a voice packet header can be established by sending call set-up information over an out-of-band channel between compression points in a mobile station and in the network.

WO 00/72549 A3

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 00/01330

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04L29/06 H04L12/56

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H04L H04M H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, PAJ, EPO-Internal, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 820 168 A (TEXAS INSTRUMENTS INC) 21 January 1998 (1998-01-21) page 4, line 40 -page 6, line 20 page 8, line 13 - line 28 page 9, line 22 - line 33 page 11, line 38 - line 48 page 18, line 35 - line 48 page 27, line 5 -page 28, line 53 page 39, line 20 - line 25 page 39, line 20 - line 25; figures 2B-D,3C,7B,7C	22
A	page 39, line 20 - line 25; figures 2B-D,3C,7B,7C --- -/--	1,8

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

13 February 2001

Date of mailing of the international search report

26.02.2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Heinrich, D

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 00/01330

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 841 831 A (AT & T CORP) 13 May 1998 (1998-05-13) column 1, line 5 -column 4, line 30; figures 2B-D,3C,7B,7C column 5, line 50 -column 6, line 17; figures 2B-D,3C,7B,7C column 7, line 15 - line 35; figures 2B-D,3C,7B,7C column 7, line 15 - line 35; figure 1 column 7, line 15 - line 35; figure 1	22
Y		1-4,6,8, 13
A	column 7, line 15 - line 35; figure 1 ---	5,7
Y	WO 98 37665 A (VAZIRI FARAMARZ ;WIMSATT JOHN D (US); FONEFRIEND SYSTEMS INC (US)) 27 August 1998 (1998-08-27) page 1, line 6 -page 3, line 1; figure 1 page 5, line 4 -page 6, line 21; figure 1 page 8, line 4 - line 10; figure 1 page 10, line 22 -page 11, line 1; figure 1 page 17, line 8 - line 10; figure 1 page 18, line 4 -page 19, line 9; figure 1 page 28, line 7 -page 29, line 5; figure 1 page 39, line 12 - line 22; figure 1 page 43, line 19 -page 44, line 12; figure 1 page 43, line 19 -page 44, line 12; figure 2A page 43, line 19 -page 44, line 12; figure 2A ---	1-4,6,8, 13
A		5,7,22
Y	S.CASNER,V.JACOBSON: "Compressing IP/UDP/RTP Headers for Low-Speed Serial Links" NETWORK WORKING GROUP, February 1999 (1999-02), pages 1-22, XP002121319 cited in the application the whole document ---	1,4,6,8, 13
A		2,3,5,7
Y	SRIDHAR T PAI: "IP Telephony: Need for Standards" VOICE & DATA, 21 May 1999 (1999-05-21), pages 1-3, XP002121320 the whole document line 12; figure 2A ---	1,4,6,8, 13
A		2,3,5,7
	--- -/--	

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 00/01330

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 5 841 854 A (MELAMPY PATRICK J ET AL) 24 November 1998 (1998-11-24) column 1, line 13 - line 16; figure 2A column 4, line 20 - column 6, line 8; figure 2A column 7, line 36 - line 42; figure 2A column 8, line 25 - line 36; figure 2A column 10, line 47 - column 12, line 34; figure 2A column 13, line 31 - column 14, line 4; figure 2A column 15, line 10 - line 13; figure 2A column 16, line 36 - line 43; figure 2A column 18, line 1 - line 7; figure 2A -----</p>	1,8,22
A	<p>EP 0 917 328 A (LUCENT TECHNOLOGIES INC) 19 May 1999 (1999-05-19) page 1, paragraph 8 - line 7; figure 2A page 6, paragraph 31 - line 7; figure 2A page 7, paragraphs 38,39 - line 7; figure 2A page 11, paragraphs 68,69 - line 7; figure 2A page 15, paragraph 94 - line 7; figure 2A page 17, paragraph 115 - line 7; figure 2A page 18, paragraphs 117,126 - line 7; figure 2A page 22, paragraphs 155,157 - line 7; figure 2A page 24, paragraphs 161,162 - line 7; figure 2A page 26, paragraph 166 - line 7; figure 2A page 30, paragraph 191 - line 7; figure 2A page 35, paragraph 237 - line 7; figure 2A page 35, paragraph 237 - line 7; figure 2A -----</p>	1,8,22

INTERNATIONAL SEARCH REPORT

International application No.
PCT/GB 00/01330

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

As a result of the prior review under R. 40.2(e) PCT,
no additional fees are to be refunded.

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☒ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/SA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-16,22

A device and a method for a packet switching radio network to provide voice services, where said device and method operate according to RTP/UDP/IP, and where said device and method comprise out-of-band signalling and compression of transmittable material.

2. Claims: 17-21

A method for compressing and decompressing headers, where said method comprises utilizing increasing counts and timestamps for performing said decompression.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 00/01330

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0820168 A	21-01-1998	US 6002722 A JP 10154949 A	14-12-1999 09-06-1998
EP 0841831 A	13-05-1998	CA 2217838 A JP 10173696 A	07-05-1998 26-06-1998
WO 9837665 A	27-08-1998	AU 6666898 A EP 0966815 A	09-09-1998 29-12-1999
US 5841854 A	24-11-1998	US 5862208 A US 5566236 A	19-01-1999 15-10-1996
EP 0917328 A	19-05-1999	CA 2249817 A CA 2249830 A CA 2249831 A CA 2249836 A CA 2249837 A CA 2249838 A CA 2249839 A CA 2249862 A CA 2249863 A EP 0912026 A EP 0910198 A EP 0917320 A EP 0917318 A EP 0912027 A EP 0912012 A EP 0918417 A EP 0912017 A JP 11289353 A JP 11252183 A JP 11275154 A JP 11275155 A JP 2000022758 A JP 11275156 A JP 11275157 A JP 11284666 A JP 11331276 A	14-04-1999 14-04-1999 14-04-1999 14-04-1999 14-04-1999 14-04-1999 14-04-1999 14-04-1999 14-04-1999 28-04-1999 21-04-1999 19-05-1999 19-05-1999 28-04-1999 28-04-1999 26-05-1999 28-04-1999 19-10-1999 17-09-1999 08-10-1999 08-10-1999 21-01-2000 08-10-1999 08-10-1999 15-10-1999 30-11-1999

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
30 November 2000 (30.11.2000)

PCT

(10) International Publication Number
WO 00/72549 A2

(51) International Patent Classification⁷: H04L 29/06

45 Goldsborough Close, Swindon, Wiltshire XN5 7EP (GB).

(21) International Application Number: PCT/GB00/01330

(22) International Filing Date: 7 April 2000 (07.04.2000)

(74) Agents: WILLIAMS, David, J. et al.; Lucent Technologies UK Limited, 5 Mornington Road, Woodford Green, Essex IG8 0TU (GB).

(25) Filing Language: English

(26) Publication Language: English

(81) Designated States (*national*): AU, BR, CA, CN, ID, IN, JP, KP, KR, US.

(30) Priority Data:
99304034 25 May 1999 (25.05.1999) EP

Published:

— Without international search report and to be republished upon receipt of that report.


(71) Applicant (*for all designated States except US*): LUCENT TECHNOLOGIES INC. [US/US]; 600 Mountain Avenue, Murray Hill, NJ 07974-0636 (US).

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): YANG, Lin [CN/GB];

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR TELECOMMUNICATIONS USING INTERNET PROTOCOL



(57) Abstract: In a wireless packet switching telecommunications network, voice services are provided by having a compressor/decompressor in each mobile station to provide each voice packet with a compressed header. Voice data and signalling data are sent separately and in different data formats to the air interface. The compressed header may be an M bit and a cyclically reset timeclick_number, which is decompressed by use of a wallclock which counts reset cycles to reinstate the voice packet headers. Alternatively, RTP agents are provided at the compression and decompression points, and voice packets are sent without headers over a "high quality" network such as a frame relay or ATM network. Compression state of a voice packet header can be established by sending call set-up information over an out-of-band channel between compression points in a mobile station and in the network.

WO 00/72549 A2

METHOD AND APPARATUS FOR TELECOMMUNICATIONS
USING INTERNET PROTOCOL

Abbreviations

5 The following abbreviations are frequently used in the draft:

PSTN: Public Switched Telephone Network

TCP: Transport Control Protocol

UDP: User Datagram Protocol

RTP: Real Time Protocol

10 IP: Internet Protocol

VoIP: Voice Over IP

CD: compressor/de-compressor

CDMA: Code Division Multiplexing Access

MAC: Medium Access Control

15 RLC: Radio Link Control

GSM: Global System for Mobile communication

GPRS: General Packet Radio Service

20 1. **Field of the Invention**

This invention relates to an apparatus and method for telecommunications using Internet Protocol, and relates especially to an advantageous data compression arrangement.

25

In a wireless telecommunications network operating a packet switching technology, it would advantageous to be able to offer voice and data services using the Internet, but the need to transmit the combined headers of Real-time Transport Protocol (RTP), User Datagram Protocol (UDP) and Internet Protocol
30 (IP) in each packet header is a disadvantage. The three headers are respectively

20, 8 and 12 bytes per packet, and this 40 byte load is nearly double the voice payload of 23 bytes for 20 milliseconds in the voice coding system known as GSM FR. It is well known that wireless resource/bandwidth is more expensive than landline arrangements, and the overload of the large header load is a serious
5 drawback.

2. Brief Description of the Prior Art

10 One solution as disclosed by S Casner and V Jacobson, "Compressing IP/UDP/RTP Headers for Low-Speed Serial Links", RFC2508, <ftp://ftp.isi.edu/in-notes/rfc2508.txt> is to compress the RTP/UDP/IP headers. A protocol is defined to compress and decompress the headers, and a reduction to between 2 and 5 bytes can be achieved. However, a major disadvantage is that if a compressed
15 packet is lost it must be re-transmitted and the provision of an error-recovery facility is essential, and therefore the round-trip-time must be short if quality is to be maintained. Further, for many radio networks in which the radio bearer capacity is designed for circuit voice service so the link layer PDU size is designed to match voice payload, it is difficult to put even 2-5 more bytes into one
20 Medium Access Control (MAC) block, so that one voice frame with its compressed header may have to be transmitted in two MAC blocks, requiring extra radio resource or there may be loss of voice quality; yet again, handover may change the compression/decompression point in the network, requiring the compression state to be re-established, which needs a CONTEXT_STATE
25 message then a FULL_HEADER packet to be sent, which causes delay and packet loss.

In S Petrack, Ed Ellessen, Framedwork for Compressed RTP, Preliminary IETF draft, presented on rem-con mailing list. Feb 1996,
30 <http://www.mbone.com/lists/rem-conf.1996Q1/0259.html>, it is suggested that the

two time related fields (RTP sequence number and timestamp) can be compressed using a 1-byte "timeclick" number and a separate RTP session control is suggested to signal the static parts of the headers out of band, but no details are given of how to achieve this.

5

3. Summary of the Invention

According to the invention, a mobile station for a packet switching radio
10 network which includes a Voice over Internet Protocol application layer and Internet Protocol Stacks including Real Time Protocol, Transport Control Protocol, User Datagram Protocol and Internet Protocol layers, further comprising a compressor/decompressor to compress voice data, and means to send voice data and call signalling data separately and in different data formats to the link layer
15 and the air interface of the mobile station.

In one arrangement the compressor/decompressor is arranged between link layer (which is above the physical layer in the air interface) and the IP layer, and receives both the voice data and the call signalling data.

20

In an alternative arrangement the compressor/decompressor is arranged between the air interface and the VoIP applications layer, and receives the voice data.

25 Also according to the invention a packet switching radio network comprising a plurality of mobile stations as defined above and at least one network element in which there is compressor/decompressor means arranged to receive signals relating to compressed voice data.

30 Further according to the invention a method of operating a packet

switching radio network to provide voice services comprising separating the voice data from the call signalling and other data, whereby each voice packet containing voice data can be provided with compressed or removed RTP/UDP/IP headers.

- 5 Yet further according to the invention, a first method of compressing and decompressing headers for a packet switching network comprises providing in each compressed header a cyclically-reset timeclick_number representing the sampling time of the packet payload; increasing the timeclick_number by 1 for each sample duration time, counting the reset cycles, and from the count of reset
10 cycles and a received timeclick_number, providing a sequence number and timestamp for providing a decompressed header.

- Yet further according to the invention, a second method of compressing and decompressing headers for a packet switching network comprises removing
15 combined RTP/UDP/IP headers and placing data in RLC/MAC payload; and decompressing received packets by use of an internal clock to obtain a timestamp value, and increasing the sequence number by 1 for consecutive packets.

- Also according to the invention, a method of establishing a compression
20 state of a packet header in a packet switching network by making use of call set-up information over an out-of-band protocol.

4. Brief Description of the Drawings

25

The invention will now be described by way of example with reference to the accompanying drawings in which:

Figure 1 illustrates a wireless packet switching network based on the UMTS model.

- 30 Figures 2a and 2b shows two embodiments of the invention in a mobile

transceiver;

Figure 3 illustrates an entire communication channel;

Figures 4a and 4b illustrate alternative compression algorithms;

Figure 5 shows establishment or re-establishment of compression state;

5 and

Figure 6 shows inter-compression point handover.

10 5. Description of a Preferred Embodiment of a Mobile Station and Network

In Figure 1, a wireless mobile telecommunication system 10 comprises a number of Mobile Stations (MS) 12 and a number of base transceiver stations (Node B) 14 connected through a RNC (Radio Network Controller) 16 (all in the Radio Access Network RAN 18) to a packet Core Network (CN) 20 which consists of two elements: a SGSN (Serving GPRS Support Node) 22 and a GGSN (Gateway GPRS Support Node) 24. The CN is connected via a IP/PSTN Gateway 26, to the PSTN (Public Switched Telephone Network) 30 and to the Internet 28.

20 In this Figure the network architecture is based on the UMTS reference model.

Suppose the network 10 operates in packet switch mode. One way to implement voice service is to use VoIP technology in which VoIP application from the mobile station 12 is treated as a general IP application and coded voice is decomposed into RTP/UDP/IP packets and transmitted over the air, the RAN 18 and the CN 20 to Internet 28 or the PSTN 30 via the IP/PSTN gateway 26.

At a mobile station 12, IP-based call signalling and the Graphical User Interface of VoIP application can run in the same way as on a normal IP terminal.

The voice traffic is sent as a link layer payload with compressed or removed RTP/UDP/IP header information, as will be explained in more detail below.

Referring to Figure 2a, the up-link direction is considered from a mobile station 60 to the network. In the mobile station there is a VoIP application layer 68 from which call signalling data is sent to a TCP layer 66 and a UDP/IP layer 65. Voice data is transmitted to an RTP/UDP layer 67 and an IP layer 65.

Both call signalling data and voice data in packets are provided to a compressor 64, which compresses the combined RTP/UDP/IP headers, but the compressor does not compress the call signalling data. The two types of packet 62, 63, (compressed and uncompressed) are put in RLC/MAC protocol, and pass over the air interface 61.

To receive voice and call signalling data (the downlink direction) the process is reversed.

In the alternative arrangement for a mobile 70 shown in Figure 3b, the compressor 74 sends/receives the voice data 63 to/from VoIP application 78 while call signalling data 62 passes through normal IP layers 75, 76.

It can be seen that in both arrangements the voice and call signalling data are separated.

Figure 3 illustrates a whole system, in which a mobile 60 with its compressor 64 is connected through the air interface 61 sequentially to a Radio Access Network (RAN) 81 which tunnels or relays data between the air interface 61 and the Core Network 84, and a decompressor CD 83 in CN 82 connected to any IP host 85 via the Internet.

In the arrangements shown in Figures 2a, 2b and 3, it is assumed that the IP/UDP/RTP header information is not used for routing etc, from the mobile station 60 to the CD 83 in CN 84; instead all data including voice packets are relayed/tunnelled. It is assumed that the packets are delivered in sequence
5 between the mobile 60 and the CD 83. It is further assumed that some mechanism will be able to distinguish compressed (speech) packets from normal (uncompressed) packets, and this distinction can be maintained until CN 84 is reached.

10 The arrangement described may achieve a level of radio efficiency which is of a similar level to a circuit switched voice service provided by wireless telecommunications systems such as GSM.

It is a further advantage that no error recovery mechanism is needed, and
15 there is no inter-packet dependency for decompression, so packet loss does not cause malfunction of the compression point.

The VoIP applications 68, 78 run as if they are accessing a normal IP network although the voice packets are treated differently along part of their
20 journey – from the MS 60 to CN 84. Also, from the viewpoint of the other IP endpoint 85 (a user terminal or a IP/PSTN gateway), the elements in the RAN 81 (MS 60, Node B and RNC 80) are treated as a set as a endpoint, because the voice frames (data 63) need to travel a relatively long way before being RTP-framed at CD 83.

25

General benefits of the arrangement are that there is higher compression gain and saving of resources; that the system operates when the round-trip-time between compression and decompression is long; and that the benefits from IP-based call signalling can be kept.

6. Description of Two Preferred Algorithms

There are two compression algorithms for IP/UDP/RTP headers, one can be characterized as a "best-effort lossy compression" and another one can be characterized as "Zero header compression". Both algorithms are based on the fact that the IP/UDP/RTP headers are not used between MS 64 and CN 84.

6a. First Preferred Algorithm

The objective is to break up the interdependency of the compressed packets. Instead of sending relative values in the compressed headers (by differential coding), absolute values (timeclick numbers) are sent as suggested by Petrack. As there is no inter-relationship between compressed RTP packets, packet loss will not stop decompression from operating.

Using the first algorithm the compressed header can be only 1 byte, in comparison with 2 to 5 bytes in a known arrangement. The most important information in RTP header, the two time related fields – timestamp and sequence number, need to be retained. As pointed out in the paper by Petrack referred to above, these two fields can be replaced by a "timeclick number" (in one byte). This number assists the decompressor to put a proper timestamp (reflecting the sampling time at the mobile station 60) and sequence number. The publication suggests that instead of the conventional timestamp and RTP number, a single 1 byte "timeclick" number is sent with each packet. However, in the prior publication there was no disclosure of how to recover the timestamp and sequence number or how to establish compression states out of band.

It is assumed that there is only one VoIP session requiring

compression per terminal, thus no CID (Context ID) bits is required. The M bit in RTP header is kept and transmitted with each compressed packet.

5 **Compression-state, first algorithm.** The compression state contains the following information for a call (consisting of two RTP sessions) to be compressed: for each call-end: IP address, two port numbers (sourcing and incoming), SSRC etc. for the call: the codec used and its parameter (e.g. sampling rate and sample duration). The codec for both directions is assumed to
10 be the same. (If not then need to store them separately).

The establishment of the compression-state is via an out-of-band protocol, which can work together with the call signalling protocol, and will be described later. This protocol will also help to migrate the state information from one CD to
15 another one in the case of handover between CDs.

Compression process, first algorithm. Through the compression, three fields will be preserved in a nearly lossless way: timestamp, sequence number and the M bit. A byte (8 bits) is used for the compressed header: the first bit is used
20 for the M bit, and the other 7 bits for timeclick_ number, which represents the sampling time of the voice payload contained in the packet. It is increased by 1 every sample duration time, e.g. 20 ms for GSM6.10 coding. It will continue to be increased even in the silent period when no packets are actually sent out.

25 The fields whose information may become inaccurate through the compression are:

- The packet ID in IP v4. It is assumed that the packet ID field always increases by 1 so it does not need to be communicated .
30 When packet loss is detected the ID value is set accordingly. As

not all packet-loss can be detected so the ID value may become inaccurate.

- 5 - UDP checksum field. The checksum field is not used (set to 0) from mobile terminal 60. If it is used on the down-link direction, it is set to 0 by the CD in the network (and then the end-to-end error detection for applications that require it is disabled). Thus the error correction using the UDP checksum will be disabled.
- 10 - RTP CSRC list. For the uplink direction, the CSRC list should always be empty. For the downlink direction, it may change (e.g. in the case of conference call). For 2-party call, it will be unchanged (empty).
- 15 - Sequence number. In the case of packet loss between the mobile station and the RTP proxy, and the decompressor failed to detect it, the sequence number recovered by the RTP proxy is incorrect, which may influence the accuracy of the statistical result of packet loss rate.

20

There are two modes of accessing the compression service. One is accessed by the VoIP application directly (as shown in Figure 3(b)), by-passing the transport and network layers. The obvious benefit is the efficiency, but it may
25 need some change of the application or need a transport layer wrap up. The service access primitive for the compressor can be:

compress (M, timeclick_number, voicepayload)

30 It is straightforward to generate a compressed RTP packet with these three

data items.

Alternatively the compression service can be accessed by the network layer in a transparent way (as shown in Figure 2(a)), thus all upper layers are
5 unknown about the compression. In this case, upon receiving a packet from upper layer, it checks the fields of source/destination IP and port number also the source SSRC. These five fields will identify a RTP session and by checking these field against the compression-state table, it is decide either to compress the packet (if it is a RTP packet whose compression state already established), or treat it like non-
10 RTP, normal packet. If it is a RTP packet to be compressed, the timestamp field is mapped to a timeclick-number. Then the above service primitive can be called.

For the downlink direction, if the UDP checksum is used (non-zero), it will be ignored.
15

After a compressed RTP packet is generated, it is put in a link layer packet together with a marker telling it is a speech packet. Other non-compressed packet will be put into a link layer packet marking itself as general data packet.

20 **Decompression process, the first algorithm.**

Except for the time-related RTP header fields, recovery of the other fields are from the compression state using a similar approach to RFC 2508.

25 For the timestamp field: the major problem to solve is that the field for timeclick number is only 7 bits. The click counting will continue and can easily wrap around (reset periodically) during a single telephone call). During a silent period, if there is no packet sent by the compressor, the time elapsed for this silent period (in terms of how many cycles passed), must be detected.

In the first algorithm according to the invention, a computer clock at the CD 84 is used to count the cycles and the timeclick number is used, with reference to the clock reading, to set the timestamp field. The clock can run at a coarser granularity. For example it can be increased by 1 for every $T/4$ period assuming the maximum jitter is less than $T/4$, which is a safe assumption, where T is the time period of a cycle represented by 7 bits. It is usually several seconds, depending on the codec parameters.

Turning now to the sequence number, this number is normally increased by 1 for each consecutive packet. It is mainly used to reflect the packet loss. In the first algorithm according to the invention, a heuristic method is used to detect packet loss by checking both the increases of timeclick number and the M bit. If the timeclick number is increased by a small number other than one (say two, three etc.) but the M bit is not set, then there is likely some packet-loss. In this case the sequence number is increased by the difference of the timeclick number. In the case of the packet that carries the set M bit gets lost (then the bigger increase of timeclick number is normal, as it is silent period), the sequence number should still be increased by 1. The probability for this situation to happen is quite small. Even if this happens and the sequence number is increased by mistake, it will slightly influence the statistic result of packet-loss rate perceived by the other RTP end (a few more packets are reported to be lost).

Denotation:

sd: sample duration, the value should come from the call setup procedure, e.g. 20ms (voice in each packet)

sr: sample rate, the value should come from the call setup procedure, e.g. 8000

nb: number of bits used for the timeclick number

TS_{last}: Timestamp number for the previous packet

TS_{this}: Timestamp number for this packet

- WT_{last}**: Wallclock reading for the previous packet
WT_{this}: Wallclock reading for this packet
TN_{last}: Timeclick number of previous packet in compressed header
TN_{this}: Timeclick number of this packet in compressed header
5 **SN_{last}**: RTP sequence number of previous packet
SN_{this}: RTP sequence number of this packet
T: the time period represented using *nb* bits (a cycle period), in units of sample duration (sd)
 $T = 2^{nb}$
10 **M**: the value of the "M" bit, in compressed header

Calculating the timestamp and sequence number:

- $TSthis = Tslast + 1$, if $M = 0$ and $\Delta tick = 1$
 $= Tslast + (\Delta cycle * (2^{nb}) + \Delta tick) * sd * sr / 1000$,
15 otherwise where:
 $\Delta tick = (T + TN_{this} - TN_{last}) \bmod T$
 $\Delta wtick = W_{this} - W_{last} \bmod T$
 $\Delta cycle = (W_{this} - W_{last}) / T / \text{integer part}$
20 $\Delta cycle = \Delta cycle' - 1$, if $\Delta wtick < \Delta tick$ and $\Delta tick - \Delta wtick \geq T/2$
 $= \Delta cycle' + 1$, if $\Delta tick < \Delta wtick$ and $\Delta wtick - \Delta tick \geq T/2$
 $= \Delta cycle'$, otherwise
25 $Sn_{this} = Sn_{last} + \Delta tick$, if $\Delta tick \neq 1$ and $\Delta tick < 4$ and $M \neq 1$

6b. Second Preferred Algorithm

- The second algorithm for header compression is now described; the header
30 may be zero.

In some cases, for example, GPRS (General Packet Radio System, an overlay packet network over GSM system), the radio bearer channel is designed in such a way that it is hard to put any extra header information together with speech data. Thus we would like to investigate if it is possible to transmit voice in "raw" format (speech only), but still keep most of the benefits from IP telephony (e.g. IP based call signalling thus enable CPL, web-based call etc).

The basic idea of this solution, as shown in Figure 4b, is that considering that the path between mobile station 60 and CN 84 is over a controlled packet network (over frame relay or ATM, for example) and certain QoS will be provided (no mis-ordering, the jitter and packet-loss-rate are small so that the voice quality will not suffer on this path), it is possible completely to remove the IP/UDP/RTP headers between mobile station and CP and use a box called RTP agent as the decompressor in CN.

15

- In this case the RTP agent (up line direction) performs a role similar to the IP/PSTN gateway: for the up link direction, the voice frames from a mobile station are transmitted without any IP/UDP/RTP headers, in a way very close to the circuit-mode voice in wireless networks, e.g. in GSM, (but is over a "good" quality packet network), up to the RTP agent which adds proper headers and sends them off to VoIP networks. On the downlink direction, the RTP agent strip off the headers and transmit them up to the mobile station.

25

Using the second algorithm, the benefit of IP based call signalling and service creation is retained. At the same time there is the benefit of high radio resource efficiency. On the other hand, the mobile terminal may lose some capability relying on RTP header information; for example to find the packet-loss-rate and packet delay, and the play buffer may be adjusted accordingly.

30

15.

The major differences between the first and second algorithms are that, when using the second algorithm:

- 5 - On the mobile station, the VoIP application loses the chance of using any time-related information in RTP header. For example to detect the packet-loss and calculate the jitter. Note that the compression itself will not introduce extra packet-loss and jitter. It would be difficult to generate proper RTCP packets but can ask RTP agent to do this job on its behalf.
- 10 - From the viewpoint of the other IP endpoint of the call (a user terminal or gateway), the packet loss detected by the RTP agent (and reflected in the fields of sequence number and timestamp) may be less accurate than the first algorithm.

15

The way that the CD in the second algorithm adds on (up link) and strips off (down link) IP/UDP/RTP headers is similar to that used in a general IP/PSTN media gateway. The differences are:

- 20 - The general media gateway normally has two network interfaces: one for PSTN and another one for packet network (e.g. IP, ATM). It translates media between circuit-mode and packet-mode. RTP-agent has two network interfaces both of which are for packet network.
- 25 - In general media gateway, the voice coming from the PSTN side is continuous and its rate is constant. In our case, as voice frames are transmitted over packet network on both sides, it needs to do more; to try to detect the packet loss in order to put on correct sequence
- 30 - numbers and timestamps by examining the inter-arrival time of the

packets from RAN side; it may need to send RTCP packets on behalf of the mobile terminal.

Compression-state, second algorithm. This is the same as in the RTP-
5 proxy approach.

Compression process, second algorithm. The compression process is very simple: it just strips off any header and puts the speech data only into RLC/MAC messages. The service access primitive for the compressor can be:
10

compress (voicepayload)

Like in RTP-proxy approach, the compression service, at the terminal, can be accessed by the network layer in a transparent way. In this case, upon
15 receiving a packet from the network layer, it checks the fields of source/dest IP and port number, also the source SSRC. These five fields will identify a RTP session and by checking these fields against the compression-state table, it is decided either to compress the packet (if it is a RTP packet whose compression state already established), or treat it like non-RTP, normal packet. If it is a RTP
20 packet to be compressed, the headers are strip off and the above service primitive can be called.

For the downlink direction, the CD in the network checks each packet to see if it belongs to a RTP session being compressed. If yes the RTP/UDP/IP
25 headers are stripped off and the speech data is put into the payload of, for example, the tunnelling protocol addressed to the right mobile terminal.

Decompression process, second algorithm. At the decompressor in the network (CD 84), a computer clock is used. As for the first algorithm, the major
30 problem is how to recover the time-related fields. There are two ways to do this:-

17.

- (a) - The decompressor checks at the beginning of every sampling duration period (the period covered by the speech frame(s) carried by an RTP packet; for example it will be 20ms if each RTP packet carries one GSM6.10 speech frame) to see if there is any compressed speech packet coming from RAN. If "yes" the decompressor adds IP/UDP/RTP headers on the packet. The decompressor maintains a small buffer for incoming speech packets from RAN to smooth out the jitter.
- 5
- 10 - The decompressor obtains the timestamp value from the internal clock (translated to the sampling time format as used in RTP). The sequence number is increased by 1 for each packet.
- (b) - Alternatively, the decompressor checks the inter-arrival time of each compressed packet arriving at the RAN side to guess if there is any packet-loss, considering the variation of delay and the possibility of silent period. After this analysis is performed, if the packet just arrived is thought as the consecutive speech packet of the previous one, then timestamp is increased in the same way as at the source (added by a constant value, which is determined by the coding scheme used, on the top of the timestamp value of the previous one). The sequence number is added by one on the top of the sequence number of the previous packet. If a packet loss is inferred then the sequence number and timestamp will be increased accordingly to reflect the gap. If a long gap is detected and a silent period is inferred, the sequence number is added by 1 but the timestamp need to reflect the gap.
- 15
- 20
- 25

While the first and second preferred algorithms have been described with reference to a packet switching radio network, both algorithms may also be

30

applied in other circumstances where the following features hold:

- The first leg between a mobile station and IP network is a point-to-point like connection over which the IP headers are not used.
- The first leg of connection guarantee in-order delivery and small jitter. Some header inaccuracy pointed out before is acceptable for the application.

7a. A preferred process of compress-state establishment and re-establishment

The compression-state establishment process is used for several purposes/occasions:

- At the beginning of a RTP session, the compression-state needs to be established to start compression and decompression.
- When inter CDs handover happens, the compression-state needs to be migrated to the new CD from mobile terminal and/or from the old CD.

The compression-state contains the following information: IP address and SSRC for both call ends, two pairs of RTP (UDP) port numbers, payload type, sampling rate, sample duration, etc.

It is assumed that the voice coding for both directions are the same, otherwise they need to be stored separately.

The compression state establishment and re-establishment are done using an out-of band protocol, which is shown in Figure 5, which shows a mobile station compressor 90 connected to a VoIP call control layer 92 under third party control; a serving network CD 94 and another network compressor 96; and the network CDs 94, 96 are connected directly by an out-of-band link 98, and are also connected to a VoIP call control layer 100 and a mobility management layer 102 under third party control.

All the CDs 90, 94, 96 are in reality compressor/decompressors.

10

The CDs 90 at the mobile station and 94 in the network have a control interface. Both CDs listen on a known port to accept instructions to start/stop compression and receive state information from the third party. Typically the instruction and information come from the voice application at MS and/or signalling gateway (e.g. a 4.323 Gatekeeper or SIP (Session Initiation Protocol) server) inside network. (Assume that the IP address of the serving CD is known to the signalling gateway.)

15

There are six messages defined between CD and a third party control or between two CDs (not including the acknowledgement messages):

20

1. STATE_START. This message indicates that a new compression session and its state is to be established. It should contain an identity of the MS being involved in the session. As an option it can contain a full (uncompressed) RTP packet so that the compression state information can be extracted from it.
2. STATE_INPUT. This message provides or modifies values of state attributes. It contains a list of (attribute_name, value) pair.

25

3. STATE_ENQRY and STATE_ENQRY_RPL. These two messages can be used to inquiry the state information and to know if it is ready to perform compression/decompression tasks.
- 5 4. STATE_HANDOVER. This message informs a current serving CP to send state information to a new CP, or asks a new serving CP to acquire state information from a previous serving CP. The message contains information bout the IP address of old and new CPs and the identity of the MS involved.
- 10 5. STATE_STOP. This message deletes a compression state. A compression can also be deleted by compressor itself when necessary.
- 15 The message STATE_INPUT is also used between the compressor 90 at MS and the CD 94, 96 in network to exchange state information. So the information available at one end will be available at the other end by using this protocol.
- 20 The messages STATE_INPUT and STATE_ENQRY are also used for moving state information from one CD to another in the case of handover. Apart from the state elements listed above, some extra information such as local clock reading is also exchanged to the new CD.
- 25 It is allowed for the compressor to pick up values or use default values for some attributes in some circumstances.

This process also supports the state re-establishment between CDs at MS and in network. This is necessary when the state information is damaged or lost at
30 one side. Once the compressor at CD or MS detects the miss or incompleteness of

state information, it can use STATE_ENQRY to obtain the state information from the other end.

While the inventive process of establishing or re-establishing compression state has been described with reference to a packet switching radio telecommunications network, the process may also be used for any compression process for a connection oriented application such as VoIP and multimedia sessions.

8. **Two preferred processes for handover between two compression-points**

One problem to use the compression scheme presented in RFC2508 within wireless networks is the impact of mobility. When a handover occurs, it is possible that the serving CD will change. So the compression states stored in the CD before handover have to be moved to or re-established at the new CD.

Two alternative approaches are proposed to cope with this problem:

- Firstly, we can arrange some communication between two CDs so that they can exchange compression states, as shown in Figure 6 in which a mobile station having a compressor 104 is handed over from a serving CD in network 106 to a new CD 108 in network. The serving and new CDs 106, 108 are provided with an out-of-band communication channel 110.

- One way is to share the compression state information among a group of CDs (which may potentially become the serving CD after handover), so that when handover happens the necessary compression context already ready in the new CD. The cost of this method is the CPU time and

memory required to receive/store the context which may not be used at all.

- 5 - Another way is to exchange the contact information during handover. To apply this approach, we need the co-operation from the handover mechanism so that the exchange of compression states information can be triggered when the CD is changed.

- 10 - A third way is to make use of soft-handover feature available in CDMA networks. The exchange of context can be performed during soft-handover period. This approach requires the co-operation from the radio network so that the two CDs can be informed when a soft-handover happens.

- 15 To allow the decompression process at the new CD, the exchange of compression-state information should include the timestamp value and sequence number value in the last decompressed RTP packet by the previous CD. The two computer clocks at the previous and new CD need not be synchronized. When the new CD start to serve the RTP session
20 handed over, it read its own clock and uses the reading as the clock reading for the last packet.

- 25 • Secondly, as in UMTS and GPRS situation, the user IP will not be used until the point to leave CN for backbone network(a tunnelling protocol is used to transport user packet between BSS and CN). Therefore we can make use of this feature and put CP at the edge of CN, for example at GGSN so that the CP is transparent to the handover. In particular, by moving the CP into CN, the CP and the IP/PSTN gateway, which is required to make use the VoP service
30 network, can be integrated. The drawback of this approach is the

possible performance bottleneck at the CP in network.

Several modifications of the present invention will become readily apparent to those skilled in the art in the light of the foregoing disclosure.

- 5 Therefore, the scope of the present invention should be interpreted from the following claims, such claims being read in the light of the disclosures.

CLAIMS

1. A mobile station for a packet switching radio network which includes a Voice over Internet Protocol application layer and Internet Protocol Stacks
5 including Real Time Protocol, Transport Control Protocol, User Datagram Protocol and Internet Protocol layers, further comprising a compressor/decompressor to compress voice data, and means to send voice data and call signalling data separately and in different data formats to the link layer and the air interface of the mobile station.
10
2. A mobile station according to Claim 1 in which the compressor/decompressor is arranged between the link layer and the IP layer. the compressor/decompressor receiving both the voice data and the call signalling data.
- 15 3. A mobile transceiver according to Claim 1 in which the compressor/decompressor is arranged between the link layer and the Voice over IP layer, the compressor/decompressor receiving the voice data.
4. A packet switching radio network comprising a plurality of mobile stations
20 according to any one of Claims 1 to 3 and at least one network element in which there is compressor/decompressor means arranged to receive compressed voice data.
5. A network according to Claim 4 in which the compressor/decompressor is
25 arranged towards the edge of the core network adjacent the backbone network.
6. A network according to Claim 4 or Claim 5 in which the voice and data packets are routed through the Internet.
- 30 7. A network according to Claim 5 or Claim 6 in which the voice and data

packets are routed through a gateway to the public switched telephone network.

8. A method of operating a packet switching radio network to provide voice services comprising separating voice data from call signalling and other data,
5 whereby each packet containing voice data can be provided with compressed or removed RTP/UDP/IP headers.
9. A method according to Claim 8 in which the voice packets for VoIP applications are sent as a link layer payload directly without going through IP
10 layers.
10. A method according to Claim 8 or Claim 9 in which each voice packet header comprises a cyclically-reset timeclick_number representing the sampling time of the packet payload; the timeclick_number being increased by 1 for each
15 sample duration time; and in which the headers are decompressed by counting the reset cycles by means of a separate clock; together with the received timeclick_number to provide the sequence number and timestamp of a decompressed header.
- 20 11. A method according to Claim 8 or Claim 9 comprising in a mobile station removing combined RTP/UDP/IP headers and placing voice data in RLC/MAC payload; and decompressing received voice packets by using an internal clock to obtain a timestamp value, and increasing the sequence number by 1 for consecutive packets.
- 25 12. A method according to Claim 8 or Claim 9 comprising, in a mobile station, removing combined RTP/UDP/IP headers and placing voice data in RLC/MAC payload; and decompressing received voice packets by determining packet inter-arrival times to detect loss of any packet, and if such loss is detected,
30 adjusting the timestamp value and sequence numbers of RTP headers of

subsequently received voice packets accordingly.

13. A method according to any one of Claims 8 to 12 in which the compression state of a voice packet header is established by making use of call set-up information over an out-of-band communications protocol between a mobile station and a compression/decompression in the network.
14. A method according to any one of Claims 8 to 13 further comprising providing an out-of-band communications protocol between a serving compressor/decompressor in the network and other compressor/decompressors in the network, and, on handover of the call, exchanging compression context information relating to a current call between the serving compressor/decompressor and a new serving compressor/decompressor.
15. A method according to Claim 14 in which the exchanged compression context information includes the timestamp value of the last decompressed RTP packet.
16. A method according to Claim 15 in which the network is a Code Division Multiplexing Access network having a soft-handover facility, and preparing and performing exchange compression context information during a soft-handover period.
17. A first method of compressing and decompressing headers for a packet switching network comprises providing in each compressed header a cyclically-reset timeclick_number representing the sampling time of the packet payload; increasing the timeclick_number by 1 for each sample duration time, counting the reset cycles, and from the count of reset cycles and a received timeclick_number, providing a sequence number and timestamp for providing a decompressed header.

18. A method according to Claim 17 further comprising including in each compressed header an M bit; and decompressing a header when no M bit is received by increasing the packet sequence number of the decompressed header by the difference of the timeclick_numbers between the packet for which no M bit is received and the last previously received packet having an M bit.
19. A second method of compressing and decompressing headers for a packet switching network comprises removing combined RTP/UDP/IP headers and placing data in RLC/MAC payload; and decompressing received packets by use of an internal clock to obtain a timestamp value, and increasing the sequence number by 1 for consecutive packets.
20. A second method according to Claim 19 in which the network is a frame relay network.
21. A second method according to Claim 19 in which the network is an Asynchronous Transmission Mode network.
22. A method of establishing a compression state of a packet header in a packet switching network by making use of call set-up information over an out-of-band protocol.

1/6





FIG. 2a
Compression accessed by IP





FIG. 2b
Compression accessed by APPS



3/6

FIG. 4a





FIG. 4b



5/6





FIG. 6



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.